

FIGURE 1

ID	<u>42</u>	CLASS	<u>44</u>	TYPE	<u>46</u>	MAX	<u>48</u>	DSC	<u>50</u>	VALID	<u>52</u>	BACKUP	<u>40</u>
REPLACEMENT OFFSET	<u>62</u>	REPL INDEX	<u>64</u>	DATA OFFSET	<u>66</u>	TRAN	<u>68</u>	VREP	<u>70</u>	RDY	<u>72</u>	LINK	<u>60</u>

REPLACEMENT OFFSET	<u>76</u>	REPL INDEX	<u>78</u>	ORIGINAL UNIT	<u>80</u>	TRAN	<u>82</u>	VREP	<u>84</u>	TYPE	<u>86</u>	<u>74</u>
REPLACEMENT OFFSET	<u>76</u>	REPL INDEX	<u>78</u>	ORIGINAL UNITS HEADER	<u>90</u>	VREP	<u>92</u>	TYPE	<u>94</u>	<u>88</u>	<u>86</u>	<u>88</u>

FIGURE 2A

HANDLE	<u>24</u>	VALID	INVALID	REPLACE	REPLACE INDEX	<u>20</u>	
Block ID	<u>26</u>	Handle Index	<u>28</u>	<u>30</u>	<u>32</u>	<u>34</u>	<u>36</u>

REPLACEMENT

22

FIGURE 2B

FIGURE 3A

© 2002 IEEE. All rights reserved.





FIGURE 3B







FIGURE 3C

FIGURE 4






FIGURE 5A




FIGURE 5B

009251545 • J23000




FIGURE 5C




FIGURE 6